



NEW!

SATURNO L SE

 (Cod. XL 06)

 3 varianti colore
 3 colour versions


Tubo verde trasparente in PVC-P, con spirale di rinforzo in PVC rigido antiurto color avorio. Interno completamente liscio, esterno leggermente corrugato. **Molto flessibile anche alle basse temperature.** Robusto e resistente allo schiacciamento, agli agenti atmosferici ed a numerose sostanze chimiche.


• In agricoltura, eccellente per aspirazione di liquidi in genere, particolarmente adatto su macchine per trattamento liquami. Versione colore disponibile su richiesta

*Transparent green PVC-P hose reinforced with an ivory anti-shock rigid PVC spiral. Inside surface smooth, light corrugation outside. **Very flexible even at low temperatures.** Strong, resistant to crushing, atmospheric agents and most chemicals.*

• *Excellent in agriculture, for irrigation and suction of liquids; suitable to be used on slurry machines. Different colour versions available on request.*

Spirale in PVC rigido antiurto
 Anti-shock rigid PVC spiral

Tubo in PVC-P / PVC-P hose



Scheda tecnica / Technical data

| Codice | Ø Int. | Spess. Min. | Spess. Max | Peso | P.E. | P.S. | Depr. | R. Curvatura | Lg. Rotolo | Vol. |
|----------------|-------------|--------------|--------------|--------|-------|-------|--------------------|--------------|------------|----------------|
| Code | Ø Int. | Min wall th. | Max wall th. | Weight | W.P. | B.P. | Vac. | Bending | Coil lgth. | Vol. |
| | mm/inch | mm | mm | g/m | [bar] | [bar] | m H ₂ O | mm | m | m ³ |
| XL060190000000 | 19,1*/3/4" | 2,2 | 2,9 | 200 | 5,0 | 15 | 6 | 110 | 50 | 0,046 |
| XL060200000000 | 20 | 2,2 | 2,9 | 210 | 5,0 | 15 | 6 | 110 | 50 | 0,048 |
| XL060220000000 | 22* | 2,3 | 3,0 | 240 | 5,0 | 15 | 6 | 130 | 50 | 0,061 |
| XL060250000000 | 25 | 2,3 | 3,0 | 270 | 5,0 | 15 | 6 | 140 | 50 | 0,078 |
| XL060255000000 | 25,5* | 2,3 | 3,0 | 270 | 5,0 | 15 | 6 | 140 | 50 | 0,079 |
| XL060300000000 | 30 | 2,3 | 3,1 | 320 | 5,0 | 15 | 6 | 170 | 50 | 0,116 |
| XL060320000000 | 31,8/1.1/4" | 2,4 | 3,2 | 360 | 5,0 | 15 | 6 | 180 | 50 | 0,122 |
| XL060325000000 | 32,5* | 2,4 | 3,2 | 370 | 5,0 | 15 | 6 | 180 | 50 | 0,124 |
| XL060350000000 | 35* | 2,5 | 3,3 | 400 | 5,0 | 15 | 6 | 195 | 50 | 0,133 |
| XL060380000000 | 38,1/1.1/2" | 2,6 | 3,4 | 450 | 5,0 | 15 | 6 | 210 | 50 | 0,172 |
| XL060390000000 | 39* | 2,6 | 3,4 | 460 | 5,0 | 15 | 6 | 215 | 50 | 0,176 |
| XL060400000000 | 40 | 2,6 | 3,5 | 480 | 5,0 | 15 | 6 | 220 | 50 | 0,180 |
| XL060450000000 | 45* | 2,7 | 3,6 | 560 | 5,0 | 15 | 6 | 250 | 50 | 0,226 |
| XL060500000000 | 50 | 3,0 | 4,0 | 700 | 5,0 | 15 | 6 | 270 | 50 | 0,251 |
| XL060520000000 | 50,8/2" | 3,0 | 4,0 | 710 | 5,0 | 15 | 6 | 270 | 50 | 0,254 |
| XL060550000000 | 55* | 3,0 | 4,0 | 760 | 5,0 | 15 | 6 | 310 | 50 | 0,454 |
| XL060570000000 | 57* | 3,0 | 4,0 | 790 | 5,0 | 15 | 6 | 310 | 50 | 0,374 |
| XL060600000000 | 60 | 3,0 | 4,2 | 860 | 5,0 | 15 | 6 | 330 | 50 | 0,394 |
| XL060630000000 | 63,5/2.1/2" | 3,0 | 4,2 | 910 | 5,0 | 15 | 6 | 350 | 50 | 0,414 |
| XL060650000000 | 65* | 3,1 | 4,3 | 960 | 5,0 | 15 | 6 | 360 | 50 | 0,636 |
| XL060700000000 | 70*/2.3/4" | 3,2 | 4,5 | 1040 | 4,0 | 12 | 6 | 450 | 50 | 0,683 |
| XL060750000000 | 75* | 3,3 | 4,6 | 1140 | 4,0 | 12 | 6 | 500 | 50 | 0,727 |
| XL060760000000 | 76,2/3" | 3,3 | 4,6 | 1160 | 4,0 | 12 | 6 | 500 | 50 | 0,738 |
| XL060800000000 | 80 | 3,6 | 5,0 | 1330 | 4,0 | 12 | 6 | 550 | 50 | 0,922 |
| XL060900000000 | 90* | 4,2 | 6,0 | 1840 | 3,0 | 9 | 6 | 630 | 30 | 0,588 |
| XL061000000000 | 100 | 4,6 | 6,4 | 2180 | 3,0 | 9 | 6 | 710 | 30 | 0,866 |
| XL061020000000 | 102/4" | 4,6 | 6,4 | 2220 | 3,0 | 9 | 6 | 710 | 30 | 0,882 |
| XL061100000000 | 110* | 5,0 | 6,7 | 2530 | 3,0 | 9 | 6 | 720 | 30 | 1,264 |
| XL061200000000 | 120* | 5,0 | 6,8 | 2770 | 3,0 | 9 | 6 | 730 | 30 | 1,368 |
| XL061250000000 | 125* | 5,1 | 6,9 | 2950 | 3,0 | 9 | 6 | 740 | 30 | 1,421 |
| XL061270000000 | 127*/5" | 5,1 | 6,9 | 2990 | 3,0 | 9 | 6 | 740 | 30 | 1,442 |
| XL061500000000 | 151,5* | 5,9 | 7,8 | 4100 | 3,0 | 9 | 6 | 800 | 20 | 1,337 |
| XL061520000000 | 152,4*/6" | 5,9 | 7,8 | 4120 | 3,0 | 9 | 6 | 800 | 20 | 1,344 |
| XL062000000000 | 200* | 6,5 | 10,0 | 6420 | 2,0 | 6 | 4,5 | 1000 | 10 | 1,760 |
| XL062030000000 | 203,2*/8" | 6,5 | 10,0 | 6520 | 2,0 | 6 | 4,5 | 1000 | 10 | 1,786 |

*Disponibile su richiesta, per quantitativi da concordare con l'ufficio vendite / *Available on request, contact our sales office for more info and quantities

I dati tecnici qui riportati sono stati misurati a 23°C e al 50% di umidità / The technical data here reported were measured at 23°C with 50% humidity